

# KUNARK HITECH MACHINING & SALES PVT.LTD.



Kunark House, 269, Kunark Marg, Kaman Bhiwandi Road, Kaman,

Vasai Road (East), Dist: Thane -401208, Maharashtra, India.

Mobile: (+91) 9867973046 Factory: 0250-6454895

Email: [info@jkgears.com](mailto:info@jkgears.com), [dalbirbright@gmail.com](mailto:dalbirbright@gmail.com) website: [www.jkgears.com](http://www.jkgears.com)









<b>Machine Id</b>	<b>:- 927</b>	<b>Serial No</b>	<b>:- 18075</b>
<b>Category</b>	<b>:- Gear Related Machines</b>	<b>Model</b>	<b>:- SRS 400</b>
<b>Country</b>	<b>:- Germany</b>	<b>Make</b>	<b>:- Hurth</b>
<b>Type of Machine</b>	<b>:- universal shaver cutter grinding machine with (Indexing plates 80)</b>	<b>Year</b>	<b>:- 1985</b>
<b>Weight</b>	<b>:- 4200.0</b>	<b>Dimensions</b>	<b>:-</b>
<b>Power</b>	<b>:- 3KW</b>	<b>Location</b>	<b>:- Mumbai Warehouse,India</b>

Specification :-

**No.of teeth 13 to 240**

**Pitch block Dia 73 to 320 mm**

**Module range 1to12**

**Shaver cutter Dia 64mm min., max.320 mm**

**Shaver cutter width, max. 40 mm**

**Grinding wheel swivelling (pressure angle) 5 to 21 Degree**

**Grinding slide swivelling (helical angle) 2x35 Degree**

**Grinding slide adjustment, vertical 240 mm**

**Cutting speed 1, 0.5, 0.25 m per min**

**Speeds of workpiece slide 5, 20, 30, 40 teeth per min.**

**Grinding slide speed 690 rpm**

**Grinding slide Dia 762 mm**

**Spindle drive 1.1 kW**

Description :-

**Gear Shaving Cutter Grinder complete with 80 xIndex Plates (20, 28, 32, 33, 40, 43,**



46, 49, 51, 52, 53, 59, 60, 64, 69, 76, 97, 116, 118, 121, 146, 156, 28, 30, 41, 50, 57, 64, 71, 79, 84, 92, 94, 99, 110, 120, 127, 147, 41, 57, 61, 63, 63, 73, 83, 113, 121, 136, 137, 146, 77, 47, 74, 75, 44, 43, 37, 31, 55, 89, 71, 95, 41, 67, 24, 78, 86, 89, 50, 85, 127, 136, 119, 150, 154, 146, 149, 128, 157, 139)

Swivelling Aluminium blocks and steel bands ,manderels etc.

The machine is Ex European Gear Shaver Cutter manufacturers and regrinders of used cutters.

It is also suitable for master gears as well as cutters for gear shapers.

<b>PITCH BLOCK DETAILS</b>			
1	4.220	8	110.41.182.00.9
2	5.235	9	110.41.174.00.9
3	5.931	10	110.41.242.00.9
4	4.441	11	110.41.186.00.9
5	162 M/M	12	110.41.166.00.9
6	193 M/M	13	110.41.212.00.3
7	110.41.175.00.3	14	H 52768 BP 86224